



linear dimension(Tolerances Standard GB/T 14486-2008)								—	▱	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60


REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
A	新发行		CLF	26.09.30











UL/CUL 技术参数
UL/CUL Technical Data

等 级 Use Group	B	C	D
额定电压 Rated Voltage [V]	300	/	300
额定电流 Rated Current [A]	12	/	10
耐 电 压 Withstanding Voltage	AC1600V/ 1 min		
接线范围 Wire Range 单/多芯线 Solid/Stranded [AWG]	26-14		

IEC 技术参数
IEC Technical Data

过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	250	400	630
额定电流 Rated Current [A]	15	15	15
额定冲击电压 Impulse withstand voltage [KV]	4		
导线截面积 Conductor cross section 硬质/柔性导线 Solid/ flexible [mm²]	1.5		

材 料 Material

绝缘材料 Insulation Material	热塑性材料/Thermoplastic
导体材料 Contactor Material	铜合金 Copper alloy
导体表面镀层 Contactive Coating	镀锡 Sn Plated

一般参数 Other Data

间距 Pitch [mm]	5.0
极数 Poles [P]	2～24
剥线长度 Stripping Length [mm]	6
螺丝Screw/扭矩 Torque(Max) [N.m]	M3/0.4
工作温度 Operating temperatur [°C]	-40～+105
引针尺寸 Pin Dimensions [mm]	4.2
PCB板孔径 PCB Hole Diameter [mm]	1.4

DES.	ZC	DATE	26.09.30	单位/UNITS	mm	尺寸/SIZE	A4	比例/SCALE	1:1	第三视角/THIRD ANGLE PROJECTION
CHK.	SJD	DATE	26.09.30	KEFA® 慈溪市科发电子有限公司 CIXI KEFA ELECTRONIC CO., LTD						版本/REV A
APP.	CLF	DATE	26.09.30							名称/TITLE KF127HH-5.0