






linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



PCB Layout



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
A	新发行		CLF	22. 02. 19
B	版本更新		CLF	26. 08. 30

UL/CUL 技术 参数				
UL/CUL Technical Data				
等 级	Use Group	B	C	D
额定电压	Rated Voltage	[V]	600	600
额定电流	Rated Current	[A]	65	65
接线范围	Wire Range	-		
单/多芯线	Solid/Stranded			
耐电压	Withstanding Voltage	AC2200V/1Min		
IEC 技术参数				
IEC Technical Data				
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	2	2	2
额定电压	Rated Voltage	[V]	1000	1000
额定电流	Rated Current	[A]	57	57
额定冲击电压	Impulse withstand voltagea	[KV]	8.0	8.0
导线截面积	Conductor cross section	-		
硬质/柔性导线	Solid/ flexible			
材 料 Material				
绝缘材料	Insulation Material	PA66		
阻燃等级	Imflamability	UL94V-0		
导体材料	Contactior Material	铜合金 Copper alloy		
导体表面镀层	Contactive Coating	镀锡 Tin Plated		
一般参数 Other Data				
间距 Pitch	[mm]	10.16		
极数 Poles	[P]	2-12		
剥线长度	Stripping Length	[mm]	-	
螺丝 Screw/扭矩 Torque(Max)	[N.m]	-		
工作温度	Operating temperatur	[°C]	-40~+105	
引针尺寸	Pin Dimensions	[mm]	4.0	
PCB板孔径	PCB Hole Diameter	[mm]	1.8	
安装类型	Mounting type	波峰焊/Wave soldering		

DES.	ZC	DATE	26.08.30
CHK.	SJD	DATE	26.08.30
APP.	CLF	DATE	26.08.30

单位 / UNITS	mm	尺寸 / SIZE	A4	比例 / SCALE	1:1	第三视角 / THIRD ANGLE PROJECTION	版本 / REV	B
							名称 / TITLE	KF2EDGSV-10.16



慈溪市科发电子有限公司
CIXI KEFA ELECTRONIC CO., LTD